



Dropleg^{UL}



Underleaf spraying system for broadcast and row applications.

Advantages

- Fits all booms
- Gentle on plants because of lateral free swinging tube
- Less weather-dependent use due to low-drift application on crop
- Optimum plant protection product deposition at the sides and from below on the leaf undersides and stalks
- Variable nozzle equipment with plant protection and liquid fertilizer nozzles
- Robust, light and flexible – only approx. 400 g



G 1994



Template
Order no. 092.163.42.10.30

Nozzle equipping:
FT, IDKT, DF, TwinSprayCap
 - ID3
 - IDK/IDKN
 - LU
 - FT



Material

POM fibre glass reinforced, PE, PA, stainless steel



Pressure range

Max. 8 bar

Application areas



Plant protection products and growth regulators



Vegetable growing



Liquid fertilizer

Order no. 092.171.56.00

Delivery contents: Preassembled without nozzles, nozzle strainer, gasket and bayonet cap

Designation	Photo	Order no.
TwinSprayCap, System MULTIJET, for flood nozzles		092.163.56.10
Nozzle strainer 60M		065.257.56.00
Y-MULTIJET-Connector 45° forward angling of nozzle		A.402.916.01
MULTIJET-bayonet cap 1/4" NTP female		A.402.910.01
Double nipple 1/4" male		095.019.30.00.42
Double swivel nozzle holder 1/4" female* Free adjustable forward angling of nozzle		A.404.172

* For combined application of standard / spray boom + Dropleg^{UL}



Dropleg^{UL} calculator



Dropleg^{UL} Flyer

