



**NOTE:** SCREEN CAN BE EASILY REMOVED FOR CLEANING BY UNSCREWING BOWL FROM HEAD BY HAND

**MAXIMUM RECOMMENDED PRESSURE:** 150 PSI (10 bar) @ 100°F (38°C) MAX.

STRAINER NO.	PIPE CONN. (F)	SCREENS*			NET WEIGHT	APPROX. FLOW RATE WITH 5 PSI (0.35 bar) PRESSURE DROP
		MESH SIZE	OPENING	FULL AREA		
AA122-1/2-PP	1/2" NPT	16	.045" (1.1 mm)	7.7 SQ. IN. (49.7 cm <sup>2</sup> )	3 1/2 oz. (0.1 kg)	12 GPM (45 l/min.)
AAB122-1/2-PP	1/2" BSPT	30	.021" (0.53 mm)			
AA122-3/4-PP	3/4" NPT	50	.011" (0.28 mm)			
AAB122-3/4-PP	3/4" BSPT	80	.007" (0.18 mm)			
		100	.006" (0.15 mm)			16 GPM (60 l/min.)

\* 50, 80, AND 100 MESH SCREENS REINFORCED WITH POLYPROPYLENE RIBS.

**DESCRIPTION:**

NO. AA122-1/2-PP AND  
NO. AA122-3/4-PP  
LIQUID STRAINERS



**Spraying Systems Co.®**

Spray Nozzles and Accessories  
P.O. Box 7900 - Wheaton, IL 60189-7900

Rev. No. 3

Data Sheet No.

122-PP

Ref.

SHEET OF