



**FEATURES:**

- POLYPROPYLENE HEAD AND BOWL WITH TYPE 304 STAINLESS STEEL SCREEN
- M6x1 METRIC THREAD MOUNTING CONNECTIONS (METAL THREAD INSERTS)
- BOWL EASILY REMOVED BY HAND TO CLEAN SCREEN
- MAXIMUM PRESSURE - 150 PSI (10 bar) AT 100°F (38°C) MAX.

STRAINER NO.	PIPE CONN. (F)	SCREENS*				NET WEIGHT	APPROX. FLOW RATE WITH 5 PSI (0.35 bar) PRESSURE DROP
		MESH SIZE	OPENING	COLOR CODE	FULL AREA		
AA122ML-1/2-PP	1/2" NPT	16	.045" (1.1 mm)	NONE	7.7 SQ. IN. (49.7 cm <sup>2</sup> )	4.1 oz. (0.12 kg)	12 GPM (45 l/min)
AAB122ML-1/2-PP	1/2" BSPT	30	.021" (0.53 mm)	YELLOW			
AA122ML-3/4-PP	3/4" NPT	50	.011" (0.28 mm)	RED			
		80	.007" (0.18 mm)	BLUE			
AAB122ML-3/4-PP	3/4" BSPT	100	.006" (0.15 mm)	GREEN			16 GPM (60 l/min)
		200	.003" (0.08 mm)	ORANGE			

\* 50, 80, AND 100 MESH SCREENS REINFORCED WITH POLYPROPYLENE RIBS

**DESCRIPTION:**

NO. AA122ML-1/2-PP AND  
NO. AA122ML-3/4-PP  
LIQUID STRAINERS WITH  
MOUNTING CONNECTIONS



**Spraying Systems Co.**<sup>®</sup>

Spray Nozzles and Accessories  
P.O. Box 7900 - Wheaton, IL 60189-7900

Rev. No. 1

Ref.

Data Sheet No.

122ML-PP

SHEET OF