



STRAINER STYLE	"A" DIMENSION
FLANGE	5.92" (150 mm)
THREADED	5.60" (142 mm)

MAX. RECOMMENDED PRESSURE: 200 PSI (14 bar) AT TEMP. 70°F (20°C).

STRAINER PART NO.*	PIPE CONN. (F)	STRAINER HEAD/BOWL MATERIAL	SCREENS				FLOW RATE WITH 5 PSI (0.35 bar) PRESSURE DROP
			MESH SIZE	OPENING	COLOR CODE	FULL AREA	
AA126ML-F75-__(-VI)	FLANGE	POLYPROPYLENE	16	.045" (1.1 mm)	GRAY	41 SQ. IN. (265 cm ²)	77 GPM (291 L/min)
AAB126ML-F75-__(-VI)	FLANGE	POLYPROPYLENE	30	.021" (0.53 mm)	YELLOW		
AA126ML-5-__(-VI)	1 1/4" NPT	POLYPROPYLENE	50	.011" (0.28 mm)	RED	41 SQ. IN. (265 cm ²)	59 GPM (223 L/min)
AAB126ML-5-__(-VI)	1 1/4" BSPT	POLYPROPYLENE	80	.007" (0.18 mm)	BLUE		
AA126ML-6-__(-VI)	1 1/2" NPT	POLYPROPYLENE	100	.006" (0.15 mm)	GREEN	41 SQ. IN. (265 cm ²)	77 GPM (291 L/min)
AAB126ML-6-__(-VI)	1 1/2" BSPT	POLYPROPYLENE	120	.005" (0.13 mm)	BROWN		

*SPECIFY -VI IN PART NUMBER FOR VITON GASKETS

DESCRIPTION:

AA(B)126ML-5-__
AA(B)126ML-6-__ &
AA(B)126ML-F75-__
LINE STRAINERS



Spraying Systems Co.[®]

Spray Nozzles and Accessories
P.O. Box 7900 - Wheaton, IL 60189-7900

Rev. No. 5

Ref.

DATA SHEET

126-PP

SHEET OF