

APDatec 144



Imprint

with imprint

Durability

refer to Soft PVC

Colour

silver grey

Food approval

No

REACH

conformity to 1907/2006/EC

RoHS

Conformity to Guideline 2015/863 (RoHs 3)

Spiral

Rigid-PVC

Material

PVC-Buna Compound

empty

144.JPG

important advices

For proper use of our products please note

Interesting facts about hoses

All technical Data are according to ISO-Standard and at 20 °C ambient and medium temperature, technical changes reserved.

APDatec 144

Nr.	Inside Diameter in mm	Outside Diameter in mm	Wall Thickness	Bending Radius	Working Pressure bar	Vacuum mmH2O	Length in m
144 025 0500	25	33,4	4,2	110	7	0,88	50
144 030 0500	30	38,6	4,3	120	6	0,88	50
144 032 0500	32	41,2	4,6	120	6	0,88	50
144 035 0500	35	44,2	4,6	120	6	0,88	50
144 038 0500	38	48	5	140	6	0,88	50
144 040 0500	40	50	5	150	5	0,88	50
144 050 0500	51	61,4	5,2	170	5	0,88	50
144 060 0500	60	71	5,5	190	4	0,88	50
144 063 0500	63	74	5,5	210	4	0,88	50
144 075 0500	76	88,4	6,2	240	4	0,88	50
144 080 0500	80	92,4	6,2	250	3	0,88	50
144 090 0500	90	102	6	290	3	0,88	50
144 100 0500	102	116,4	7,2	320	3	0,88	50
144 110 0250	110	124	7,2	410	3	0,88	25
144 125 0250	125	141	8	620	2	0,88	25
144 152 0200	152	170	9	500	2	0,88	20
144 152 0060	152	170	9	500	2	0,88	6
144 152 0040	152	170	9	500	2	0,88	4
144 152 0050	152	170	9	500	2	0,88	5
144 160 0200	160	178	9	750	2	0,88	20
144 200 0200	200	224	12	1.100	1	0,88	20
144 200 0050	200	224	12	1.100	1	0,88	5
144 200 0040	200	224	12	1.100	1	0,88	4