

APDatec 810



Imprint

with imprint

Durability

refer to Soft PVC

Colour

black

Yarn

Polyester fabric

Food approval

No

REACH

conformity to 1907/2006/EC

RoHS

Conformity to Guideline 2015/863 (RoHS 3)

Material

Soft-PVC

empty

810.JPG

important advices

For proper use of our products please note

[Interesting facts about hoses](#)

All technical Data are according to ISO-Standard and at 20 °C ambient and medium temperature, technical changes reserved.

APDatec 810

Nr.	Inside Diameter in mm	Outside Diameter in mm	Wall Thickness	Working Pressure bar	Bursting Pressure bar	Length in m	Weight per Piece
810 006 50 6	6	12,4	3,2	20	60	50	6,15 kg
810 006 00 6	6	12,4	3,2	20	60	100	12,3
810 009 00 9	9	15,4	3,2	20	60	100	16,3
810 009 50 9	9	15,4	3,2	20	60	50	8,15
810 010 00 10	10	16,4	3,2	20	60	100	17,6
810 013 50 13	13	21	4	20	60	50	14,2
810 013 00 13	13	21	4	20	60	100	28,4
810 016 50 16	16	25,6	4,8	20	60	50	20,85
810 019 50 19	19	28,6	4,8	20	60	50	23,85